

Job Name:

System Reference:

Date:

**GENERAL FEATURES:**

- Dual set point functionality
- Compact floor-mount
- Two-speed settings
- Controls can be wall-mounted or unit-mounted in a hidden case

ACCESSORIES:

CN24 Relay Kit (CN24RELAY-KIT-CM3)

SPECIFICATIONS:**Capacity***

Cooling	Btu/h	6,000
Heating	Btu/h	6,700

* Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:

Cooling | Indoor : 80° F (27° C) DB / 67° F (19° C) WB

Cooling | Outdoor : 95° F (35° C) DB

Heating | Indoor : 70° F (21° C) DB

Heating | Outdoor : 47° F (8° C) DB / 43° F (6° C) WB

Electrical

Electrical Power Requirements	208 / 230V, 1-phase, 60Hz	
Minimum Circuit Ampacity (MCA)	A	0.32 / 0.34 (60Hz)

External Dimensions

Unit (H x W x D) In. (mm)	25-3/16 x 34-29/32 x 8-11/16 (639 x 886 x 220)
------------------------------	---

Net Weight

Unit	Lbs.(kg)	51 (23)
------	----------	---------

External Finish Galvanized**Coil Type** Cross fin (Aluminium fin and copper tube)**Fan**

Type x Quantity	Sirocco fan x 1	
Airflow rate (Low-High)	CFM	194 - 229
Motor Type	1-phase induction motor	

Air Filter Standard filter**Refrigerant Piping Diameter**

Liquid (High Pressure)	In.(mm)	1/4 (6.35) Flare
Gas (Low Pressure)	In.(mm)	1/2 (12.70) Flare

Field Drain Pipe Size In.(mm) I.D. 1 (26)**Sound Level**

Low-High	dB(A)	208/230V	36 - 41
----------	-------	----------	---------

Notes:

